


## Premium Military Grade Duct Tape



- Backing:** PE Coated Cloth
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Olive Drab, Black
- Specifications:** ASTM D -5486 Type IV Class 1 (supercedes PPP-T-60D & E Type IV, Class 1), DPM 871-3  
NSN 7510-00-074-4961
- Standard Sizes:** 48mm x 55m, 72mm x 55m

### Applications

- Waterproof packaging for military and aerospace applications
- Media blast protection and surface masking
- Challenging repair, bundling, and seaming applications

### Features

- PE-Coated Cloth Backing
- Natural Rubber Based Adhesive

### Benefits

- High tensile strength for difficult applications
- Extremely conformable
- Crisp, straight tear
- Moisture, solvent, and abrasion resistant
- Aggressive adhesion to all surfaces

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	12.0 mils	0.305 mm	ASTM D-1000
<b>Adhesion to Steel</b>	95 oz/in	10.39 N/cm	PSTC-101
<b>Adhesion to Backing</b>	40 oz/in	4.38 N/cm	PSTC-101
<b>Tensile Strength</b>	50 lb/in	87.56 N/cm	ASTM D-1000
<b>Elongation</b>	13%		ASTM D-1000
<b>Operating Temperature</b>	40 to 200 °F	4 to 93 °C	
<b>Total Mass Loss</b>	1.61%		ASTM E 595
<b>Collected VCM</b>	<0.01%		ASTM E 595

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.